



PRE-TREATMENT



Precise even pre-treatment of fabrics for pigment inks are essential for providing added colour gamuts and wash fastness. The GoTx[®] pre-treatment module was designed to do more than just wet fabric. A rotational dosing liquid drum lays the correct amount of pre-treatment solution to the top surface of fabric without the underside getting wet (fabric weight dependent). This results in the fabric hand and weight not changing in production.

A quad zone horizontal fixation unit dries the fabric inline so its ready to print straight from the GoTx[®] pre-treat machine. Precision liquid dosing with no misting, equates to less pre-treat needed in process.

Designed to run with the GoTx[®]2190/4190/2260 printer series, or any brand of direct fabric printers.



Intelligent controls



Precision rewind



Quad zone heaters



Dosing drum



Specifications

	1900mm	2600mm
Width x Depth x Height (mm)	2700 x 1800 x 1300 (106" x 71" x 51")	3400 x 1800 x 1300 (134" x 71" x 51")
Media size (mm)	1900	2600
Speed	20-80m ² /hour	20-80m ² /hour
Average Pre-Treat Consumption	130ml/m ² (Humidity/fabric dependent)	130ml/m ² (Humidity/fabric dependent)
Power	3 Phase, 415V	3 Phase, 415V